

# MODIFICATION INSTRUCTIONS

for the

## ***KODAK X-Omatic* MULTILOADER 700**

Service Code 3053

### MODIFICATION No. 22

#### Type 1 SELECTIVE

PURPOSE:

To reduce the amount of particles on the film.

**IMPORTANT** : Use qualified service personnel to install this modification !

**SERIAL NUMBERS** : (50Hz) all units  
: (60Hz) all units

**INSTALLATION TIME** : Approx. 0.5 hour

**PARTS REQUIREMENTS** : MOD KIT #22 PN 9195106

**PLEASE NOTE**

The information contained herein is based on the experience and knowledge relating to the subject matter gained by Kodak prior to publication.

No patent license is granted by this information.

Kodak reserves the right to change this information without notice, and makes no warranty, express or implied, with respect to this information. Kodak shall not be liable for any loss or damage, including consequential or special damages, resulting from the use of this information, even if loss or damage is caused by Kodak's negligence or other fault.

PARTS LIST

PART NO.	DESCRIPTION	QUANTITY
9195106.....	MOD KIT #	
The Kit contains:		
9212931.....	EDGE PROTECTOR (self adhesive aluminum foil).....	12
9212941.....	O-RING.....	12

INSTALLATION

1. Switch off the ML700.
2. Take off the REAR PANEL.
3. Replace the outer FOAM ROLLERS of the FILM POCKET with O-RINGS. Use 1 O-Ring for each ROLLER. See figure 2.

NOTE

O-Rings contaminated by perspiration may cause film artefacts. To avoid this wash your hands before touching the O-Rings or use gloves.

4. Fold the 8 self adhesive ALUMINUM FOILS ( EDGE PROTECTORS) and mount them from underneath to the outer BRACKETS of the FILM POCKET. This prevents the FILMS from becoming abraded by the sharp edges of the FILM POCKET BRACKETS. Mount the FOILS in position A first. Then mount the FOILS in positions B so that they overlap a little the FOILS in positions A. See figure 3.

FINAL TEST

1. Circle N0 22 on the MODIFICATION LABEL.





figure 1

2. Mount the REAR PANEL.

3. Switch on the ML700 and run a few cycles.



Replace the outer FOAM ROLLERS (marked with an arrow) with O-RINGS. Use 1 O-RING for each ROLLER.

#### NOTE

**O-Rings contaminated by perspiration may cause film artefacts. To avoid this wash your hands before touching the O-Rings or use gloves.**

figure 2




figure 3



**CUSTOMER EQUIPMENT SERVICES KODAK AG STUTTGART GERMANY**